## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade m	nark: LEDVANCE
----------------------------	----------------

Supplier's address: LEDVANCE GmbH, Parkring 29-33, 85748 Garching, DE

Model identifier: AC43879

_	•			
Typa	Λt	liaht	sourc	Δ.
IVDE	OI.	IIGIIL	<b>3</b> Uui C	c.

imal

ing

Outer dimen-

sions without

separate con-

trol gear, light-

control

Height

Width

Depth

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	constant cur-		
(or other electric interface)	rent: 700mA		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	_
	No	Liivelope.	-
High luminance light source:		D'b.l.	NI -
Anti-glare shield:	No .	Dimmable:	No
	Product para		
Parameter	Value	Parameter	Value
	General product p	arameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	31	Energy efficiency class	Е
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	4 200 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P <sub>on</sub> ), expressed in W	30,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or	80

595

595

32

the range of CRI-values that can be set

Spectral power dis-

range 250 nm to 800

nm, at full-load

in

tribution

See image

in last page

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordi-	0,382	
		nates (x and y)	0,380	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	1	Survival factor	0,90	
the lumen maintenance factor	0,70			

(a)'-': not applicable; (b)'-': not applicable;

