## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's	name	or trade mark:	LEDVANCE
------------	------	----------------	----------

Supplier's address: LEDVANCE GmbH, Parkring 29-33, 85748 Garching, DE

Model identifier: AC43880

Tν	pe	of	light	source	•:
٠,	<b>P</b> C	٠.		504.00	••

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	constant cur-		
(or other electric interface)	rent: 700mA		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

## **Product parameters**

Froduct parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
	mption in on- 00 h), rounded st integer	31	Energy efficiency class	E	
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		4 200 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500	
On-mode power (P <sub>on</sub> ), expressed in W		30,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00	
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80	
Outer dimen-	Height	595	Spectral power dis-	See image	
sions without	Width	595	tribution in the	in last page	
separate con- trol gear, light- ing control	Depth	32	range 250 nm to 800 nm, at full-load		

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordi-	0,312	
		nates (x and y)	0,328	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	1	Survival factor	0,90	
the lumen maintenance factor	0,70			

(a)'-': not applicable; (b)'-': not applicable;

