Product Information Sheet

separate con-

trol gear, light-

control

ing

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources			ora with regard to energ	5, S							
Supplier's name or trade mark: LEDVANCE Supplier's address: LEDVANCE GmbH, Parkring 33, Garching, Germany Model identifier: AC32678											
							Type of light so	urce:			
							Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type		G13									
(or other electri	c interface)										
Mains or non-mains:		MLS	Connected light source (CLS):	No							
Colour-tuneable	e light source:	No	Envelope:	-							
High luminance	light source:	No									
Anti-glare shield	d:	No	Dimmable:	No							
Product parameters											
Parameter		Value	Parameter	Value							
General product parameters:											
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		8	Energy efficiency class	E							
dicating if it refe a sphere (360º) (120º) or in a na	s flux (фuse), in- ers to the flux in , in a wide cone rrow cone (90º)	900 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000							
On-mode power (P _{on}), ex- pressed in W		8,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00							
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80							
Outer dimen-	Height	602	Spectral power dis-	See image							
sions without	Width	25	tribution in the	in last page							

range 250 nm to 800

nm, at full-load

25

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	18			
		Chromaticity coordinates (x and y)	0,382 0,380			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,90			
the lumen maintenance factor	0,70					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		If yes then replace- ment claim (W)	18			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)'-': not applicable; (b)'-': not applicable;

