## **Product Information Sheet**

sions without

separate con-

trol gear, light-

control

ing

Width

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources			
Supplier's name or trade mark	: LEDVANCE		
Supplier's address: LEDVANCE	GmbH, Parkring 33,	Garching, Germany	
Model identifier: AC32675			
Type of light source:			
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	G13		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No
	Product para		
Parameter	Value	Parameter	Value
	General product	1	
Energy consumption in on mode (kWh/1000 h), rounded up to the nearest integer		Energy efficiency class	E
Useful luminous flux (фuse), in dicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500
On-mode power (P <sub>on</sub> ), ex pressed in W	16,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby powe (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal	<i>'</i>	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimen- Height	1 212	Spectral power dis-	See image

tribution

25

25

in

range 250 nm to 800

nm, at full-load

the

in last page

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	36	
		Chromaticity coordinates (x and y)	0,312 0,328	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	0	Survival factor	0,90	
the lumen maintenance factor	0,70			
Parameters for LED and OLED mains light sources:				
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		If yes then replace- ment claim (W)	36	
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4	

(a)'-': not applicable; (b)'-': not applicable;

